

BFMP 250 H



Options

- √ Mixing and high pressure pumps can be used simultaneously.
- √ Tailor-made for a mud mixing truck in which the drill rig itself can be placed as well
- √ Hydraulic drive on truck PTO, fixed diesel engine speed
- √ Wireless remote control with Pressure reading and Liters per minute
- √ Hydraulic driven hose reel 50 meters with 1 1/4 " high pressure hose
- √ 3x 3000 liter tank for clean water, mixed product and mix tank stock.
- √ Level measurement in mix tank so the pump will automatically stop at low level (low level safety)
- √ Level measurement in storage tank so the high pressure pump will automatically stop at low level (low level safety)
- √ Use high pressure pump in combination with clean water tank to clean the machine
- √ KSB mix pump with mechanical seal

Frame	Truckconstruction
Dimensions	8200 (L (mm)) X 2450 (W (mm)) x 2200 (H (mm))
Power drive	2 PTO's MAN truck with an average power consumption of +/- 55 kw Rotational speed PTO High pressure pump 1068 RPM Rotational speed PTO mix pump 672 RPM
Hydraulic pump high pressure	Ls-pump max. 137 L/min Stroke volume 2 x 64 cm ³ /rev
Hydraulic pump mix	Ls-pump max. 68 L/min Stroke volume 101 cm ³ /rev
Mixpump	Capacity 1000 L/min @ max 5 bar
High pressure pump	Capacity 250 L/min @ max 65 bar
Controls	Stainless steel electrical box attached to the unit Teleradio remote control
Weight	2500 kg